

NEOGRAFIATO SILICONATO

WATERPROOF SILICONE PASTE FORM COATING

DEC/29 | DECORATIVE COATINGS

PROPERTIES

NEOGRAFIATO SILICONATO is a waterproof decorative acrylic finishing coating with excellent adhesion and high elasticity. It has high resistance to extreme weather conditions and due to its high elasticity, it does not crack. It can be applied on plasterboards or on polystyrene for external wall insulation system. It has great stability and is suitable for both, indoor and outdoor use.

CONSUMPTION

1mm: 1-2kg/m²

2mm: 2-3kg/m²

4mm: 3-4kg/m²

STORAGE

Up to 12 months in closed containers protected from the sun and low temperatures.

Attention: colour and general technical characteristics may vary slightly due to the substrate or by not following the manufacturer's directions for use. Technical specifications may vary slightly between product batches.

DIRECTIONS FOR USE

- Surfaces where NEOGRAFIATO SILICONATO will be applied must be free of dust and dirt.
- The surface must be applied with a coat of NEOCHROM's NEOSTRONG PRIMER diluted at 1:1 ratio with clean water. The primer needs 24 hours to dry.
- NEOGRAFIATO SILICONATO is ready to use in a thick paste form.
- Apply with a stainless-steel finishing trowel.
- Apply on the surface coated with primer.
- Few minutes later and before completely dry, work the material with a plastic finishing trowel or a grout float in quick and short movements. To achieve the desired result work towards only one direction.

TECHNICAL SPECIFICATIONS

Colour:	Wide range of made to order colours
Does not contain lead or mercury:	✓
Temperature during application:	From +5°C to +35°C
Drying time:	After 48 hours
Mixture pH:	7±1

PACKAGING

3 and 25kg plastic containers

CE
EN 998 - 1

