

NEOPAINT STANDARD

USUAL PLASTIC PAINT FOR INDOOR USE

PAI/13 | PAINTS

PROPERTIES

NEOPAINT STANDARD is a high quality vinyl emulsion-based usual paint with inert admixtures for indoor use. It is easy to apply. It is used on plaster or cement coated surfaces.

COVERAGE

Approximately 8-10m²/lt depending on the surface's absorbency.

STORAGE

Up to 12 months in sealed containers protected from direct sunlight and from low temperatures.

Attention: Colour and general technical characteristics may vary slightly due to the substrate or by not following the manufacturer's directions for use. Technical specifications may vary slightly between product batches.

DIRECTIONS FOR USE

- Surfaces must be dry and clean from all foreign materials.
- Cracks and other wear should be repair before painting.
- Sand down new surfaces and remove resulting dust with sandpaper.
- Apply with a brush, paint roller and air-brush.
- Apply 1 coat of NEOCHROM'S acrylic NEOSTRONG PRIMER diluted at 1:1 ratio with clean water for better stability, waterproofing and less absorbency.
- Apply the first coat of the paint after 2-3 hours at 20°C.
- Apply the second coat of paint after 4 hours.
- Stir well before use.

TECHNICAL SPECIFICATIONS

Colour:	Wide range of colours made to order with NEOCHROM's colour chart.
Dilution:	5% per volume with water
Reapplication time:	After 3-4 hours at 20°C
Complete drying time:	After 120 hours
Specific weight:	1,60 ± 0,05kg /lt (PN-EN ISO 2811-1:2002)
Mixture pH at 20°C:	7-8 (ISO 1148:1996)
Humidity resistance:	Excellent
Temperature during application:	From +5°C to +35°C
Viscosity:	8540 mPa.s (EN-ISO 2555:1989)
Coverage:	395.5 g/m ² for 99% coverage
Whiteness:	86,3% (EN-C-81913:1998)

PACKAGING

1, 2½, 5 and 10ltr plastic containers

