

SPRAYTEX

ACRYLIC DECORATIVE COATING WITH ROUGH-TEXTURE FINISH

DEC/33 | DECORATIVE COATINGS

PROPERTIES

SPRAYTEX is decorative/touch-up rough-textured coating. It contains copolymer emulsion and inert admixtures. It is easy to use and can be applied on brick surfaces, fair face, plasterboards and any plastered surface providing an attractive finish. It has high resistance to extreme weather conditions and to UV radiation.

COVERAGE

Depends on the desired thickness.
For a 4mm coat, 3-4kg/m² is required.

STORAGE

Up to 12 months in closed containers protected from the sun and low temperatures.

Attention: colour and general technical characteristics may vary slightly due to the substrate or by not following the manufacturer's directions for use. Technical specifications may vary slightly between product batches.

DIRECTIONS FOR USE

- Surfaces must be free from dust and dirt.
- The surface must be applied with a coat of NEOCHROM's NEOSTRONG PRIMER diluted at 1:1 ratio with clean water. The primer needs 24 hours to dry.
- Apply with a specialty machine or with air-brush.

TECHNICAL SPECIFICATIONS

Form:	Liquid paste
Colour:	White. Wide range of made to order colours
Temperature during application:	From +5°C to +35°C
Mixture pH:	9
Compressive strength:	✓

PACKAGING

25kg plastic containers

CE
EN 998 - 1

