

MARTEX ACRYLIC

100% ACRYLIC SMOOTH-SURFACE DECORATIVE COATING

DEC/24 | DECORATIVE COATINGS

PROPERTIES

MARTEX ACRYLIC is a 100% acrylic decorative coating with excellent adhesion and highly resistant to extreme weather conditions. It has high resistance to UV radiation and to humidity. It can be made in a wide range of colours and due to its special resin, it provides to the product high colour resistance since it protected from sun radiation. MARTEX ACRYLIC has an excellent workability and powerful adhesion. It can be applied mainly outdoors but also indoors.

COVERAGE

1.5-2kg/m² for 1mm.

STORAGE

Up to 12 months in closed containers protected from the sun and low temperatures.

Attention: colour and general technical characteristics may vary slightly due to the substrate or by not following the manufacturer's directions for use. Technical specifications may vary slightly between product batches.

DIRECTIONS FOR USE

- Surfaces to be treated with MARTEX ACRYLIC must be free of grease, dirt and dust.
- The surface must be applied with a coat of NEOCHROM's NEOSTRONG PRIMER diluted at 1:1 ratio with clean water. The primer needs 24 hours to dry.
- The application of the primer provides the coating with better adhesiveness and long-lasting effect.
- On the surface treated with primer, apply MARTEX ACRYLIC and press with a stainless-steel finishing trowel.

TECHNICAL SPECIFICATIONS

Colour:	Wide range of made to order colours
Specific weight:	1,65 ± 0,05 kg/l
Temperature during application:	From +5°C to +35°C
Drying time:	After 48 hours
Mixture pH:	7±1

PACKAGING

25kg plastic containers

